



DALIER® 产品选型手册

PRODUCT SELECTION MANUAL



1688.com



www.dalier.cn



个人微信

▶ WWW.DALIER.CN



COMPANY

INTRODUCTION

企业简介

乐清市达利尔电器是一家专业从事设计和开发线路终端和连接器、尼龙扎线带、电缆附件和接线端子与出色的经验生产此类产品。

Yueqing daller electrical appliance factory is specialized in designing and developing wiring terminals and connectors, nylon cable ties, cable accessory and terminal blocks with excellent experience to manufacture such products.



我们的优势

产品种类繁多

So Many Products

高纯度的材料

High Purity Material

一流的工程师

First-class Engineer

一流的设备

First-class Equipment

公司生产技术标准严格引用先进的工业和研究由美国国家电气控制 and 分配设备质量监督检测中心,是在1998年获得ISO9001国际质量体系认证。它拥有一流的设备和开发工程师,产品使用高纯度的材料,接触系列齐全,品种众多,欢迎许多客户以其优良的品质和优惠的价格!

本公司保留原则“优良的品质,超过信用,客户第一” 全心全意为大众服务的用户,我们愿意创建世界塞满品牌和产品与客户!

The company is producing strictly reference to the technical standard advanced industrial and examined by the national electrical control and distribution equipment quality supervision testing center, is have obtained iso9001 international quality system certificate in 1998. It possessing first-class equipment and developing engineers, products are made that use the high purity material. The contact series are complete, numerous in varieties, that are welcome to many clients for its excellent quality and favourable price!

Our company with holding the principle "excellent quality, exceeding credit, clients first" to serve the mass of users heart and soul. We are willing to create the world -leading brand and products with clients!

www.daller.cn

达利尔创自己的品牌
Daller create ourself brand



1998年获得ISO9001



EQUIPMENT AND PRODUCTION

设备与生产

达利尔创自己的品牌

Dalier create ourself brand



DA LIER

为保证产品质量的稳定性和可靠性，我们坚持国际质量标准体系运行，并对产品进行检测监控--我们的标准是因为我们对品牌完美的追求，我们的诸多认证不仅仅是我们的荣誉，更是我们前进的动力!

To ensure the stability and reliability of product quality, we always implement the international quality standard system, and stress on the inspection, test and monitoring of the products. Our high standard is from the pu-rsuit of perfect brand, and our many certificates acqui-red represent not only our honors, but also our advancing power.

www.dalier.cn



DALIER®



荣誉 更 是 动 力

HONOR IS MORE MOTIVATION



端头型号说明

CATEGORY INTRODUCTION

R V S 1.25 - 4



说明1 Introduction 1

110/0.110*	(2.8mm)
187/0.187*	(4.75mm)
205/0.205*	(5.2mm)
250/0.250*	(6.35mm)
312/0.312*	(8.0mm)
375/0.375*	(9.4mm)
156/0.156*	(4mm)
195/0.195*	(5mm)

说明2 Introduction 2

R	圆形端头 Ring terminal
S	叉形端头 Fork terminal
H	钩形端头 Hook terminal
PT	针形端头 Pin terminal
FD	母接头 Female connector
MD	公接头 Male connector
FR	子弹形母接头 Bullet female connector
MP	子弹形公接头 Bullet male connector
DB	片形端头 Chip terminal
LS	锁扣叉形端头 Snapclose furcate terminal
FS	凸形叉形端头 Male chip terminal
LB	凹片形端头 Female chip terminal
BV	长形中间接头 Long full terminal
FLD	旗形母接头 Flag female terminal
FDF	母全绝缘端头 Female full-insulating terminal
PVT	短形中间接头 Short middle terminal
PBD	肩背形公、母接头 Shalle shaped

说明3 Introduction 3

Wire	Wire section(mm ²)	America wire(A.W.G)
1.25	0.5-1.5	22-16
2	1.5-2.5	16-14
3.5	2.5-4	14-12
5.5	4-6	12-10
8	6-10	8
14	10-16	6
22	16-25	4
38	25-35	2
60	50-70	1/0
70	70-95	2/0
80	95-120	3/0
100	120-150	4/0
150	150-185	250/300MCM
180	185-240	300/350MCM
200	240-300	400/600MOM
325	300-400	500/600MOM

说明4 Introduction 4

Bolt pass diameter(mm)	America wire(mm)
3.2	#4
3.7	#6
4.3	#8
5.3	#10
6.4	1/4
8.4	5/16
10.5	3/8
11.0	7/8

Bolt pass diameter(mm)	America wire(mm)
130	1/2
150	9/16
170	5/8
180	11/16
210	3/4
230	7/8
250	15/16
280	1



TWO HOLE LONG BARREL COPPER LUGS

双孔长臂铜接头

■ TWO-Hole Lug long Barrel

U.L. listed per 486A upto 35KV.

Ideal for industrial, Oil rig, mining, welding & transportation termination application. Heavy duty design which permits additional crimp for added mechanical strength.

型号 ITEM NO.	尺寸 Dimension(mm)			颜色 Color	A.W.G
	d	L	L1		
2L16M6	4.8	66	35	Blue	6
2L25M6	6	87	34	Gray	4
2L35M8	7.5	10.5	36	Brown	2
2L50M8	10	13	45	Pink	1/0
2L70M12	11	14.5	47	Black	2/0
2L95M12	13.5	17.5	53	Purple	4/0
2L120M12	15	19	55	Yellow	250KCMIL
2L150M12	18	22.5	67.5	Red	350KCMIL
2L185M12	19	24	76	Blue	400KCMIL
2L240M12	21	27	76	Brown	500KCMIL
2L300M12	22.5	29	90	Green	600KCMIL
2L400M12	26	33	92	Black	750KCMIL
2L500M12	30	38	98	White	1000KCMIL



ONE HOLE LONG BARREL COPPER LUGS

单孔长臂铜接头

■ ONE-Hole Lug long Barrel

U.L. listed per 486A upto 35KV.

Ideal for industrial, Oil rig, mining, welding & transportation termination application. Heavy duty design which permits additional crimp for added mechanical strength.

型号 ITEM NO.	尺寸 Dimension(mm)			颜色 Color	A.W.G
	d	L	L1		
L10M6	5.0	7	22	RED	8
L16M6	4.8	7.5	36.5	Blue	6
L25M6	6	8.7	35	Gray	4
L35M8	7.5	10.5	33	Brown	2
L50M8	10	13	42.5	Pink	1/0
L70M10	11	14.5	47.5	Black	2/0
L95M12	13.5	17.5	53	Purple	4/0
L120M12	15	19	55	Yellow	250KCMIL
L150M12	18.5	22	67	Red	350KCMIL
L185M16	19	24	75.5	Blue	400KCMIL
L240M16	21	27	78	Brown	500KCMIL
L300M16	22.5	29	91.8	Green	600KCMIL
L400M16	26	33	95	Black	750KCMIL
L500M16	30	38	102	White	1000KCMIL

ONE HOLE OFFSET FLOATING TONGUE LUGS

单孔浮动偏舌形接头

High copper alloy terminal with offset tongue for joining a wide range of cable to equipment pads or bar. Easy to install with screwdriver or wrench. Connector is re-usable. Plain copper finish.



特性 Features	优势 Benefits
Convenient range-taking design.	Reduces catalog number. One connector accommodates several conductor sizes.
High conductivity copper alloy.	Long lasting reliable contact.
Compact design.	Easy to use, Reduces labor time.
Slot Robertson screw/hex head/hex socket bolt.	No special installation tools required. Eliminates over-torquing/potential conductor damage.






Fig.2




Fig.1




Fig.3

All size are inch.

型号 Catalog Number	图号 FIG	线径范围 Wire Range	尺寸 Dimension(mm)						螺栓孔尺寸 Stud hole size	L	螺钉型式 Screw type	螺钉尺寸 Screw size	推荐拧紧力矩 Recommendes lightening torque
			B	C	D	H	K						
KLU25	1	14-10	0.28	0.31	0.47	0.66	0.14	8	0.91	Slot Robertson	8/32	20	
KLU35	1	14-6	0.43	0.38	0.57	0.91	0.20	10	1.71	Slot Robertson	1/4	45	
KLU70	1	8-2	0.50	0.50	0.61	1.05	0.27	1/4	1.32	Slot Robertson	5/16	50	
KLU125	1	2-1/0	0.61	0.62	0.86	1.50	0.26	1/4	1.78	Slot Robertson	3/8	50	
KLU175	2	4-3/0	0.75	0.75	1.20	1.40	0.41	3/8	2.20	Hex Socket	3/8	124	
KLU225	2	2-4/0	1.00	1.00	1.24	1.64	0.34	5/16	2.54	Hex Socket	7/16	204	
KLU300	3	1/0-350	1.21	1.10	1.60	2.63	0.41	3/8	3.25	Hex Head	5/8	325	
KLU400	3	1/0-500	1.49	1.50	2.12	2.74	0.41	3/8	4.26	Hex Head	5/8	375	
KLU650	3	600-1000	1.88	2.00	1.90	3.73	0.53	1/2	4.61	Hex Head	3/4	500	